

C2	M	140	S	2	E	S	18T	0	005	A	18	T	S	A		
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15		
C2	M	190	-	S	2	E	N	14T	0	-	000	0	00	0	0	00

1 MODEL & PORT SIZE
 1 - SolidC 1 2" x 1.5"
 2 - SolidC 2 2.5"x1.5"
 3 - SolidC 3 3.0"x1.5"
 4 - SolidC 4 4.0"x2"

2 CONNECTION TYPE
 M - Tri-Clamp®(only)

3 IMPELLER Size 190(MM)

4 SEAL TYPE
 SSS - Single Shaft Seal (DG Std.) FSS
 - Flushed Shaft Seal (FG)

5 SEAL FACE MATERIAL
 2 - C vs. SC (Std.)
 4 - SC vs. SC

6 ELASTOMERS MATERIAL
 E - EPDM
 Y - Fluoroelastomer (Viton, FPM, SFY)
 U - Buna

7 LEG BRACKET
 N - No
 S - Stainless Steel

8 MOTOR FRAME
 14T - 143TC/145TC
 18T - 182TC/184TC
 21T - 213TC/215TC
 25T - 254TC/256TC
 28T - 284TC/266TC

9 PUMP OPTIONS
 0 - No options
 M - Stainless Steel Drive Ring

10 MORSE POWER
 001 - 1 HP
 1P5 - 1.5 HP
 002 - 2 HP
 003 - 3 HP
 005 - 5 HP
 7P5 - 7.5 HP
 010 - 10 HP
 015 - 15 HP
 020 - 20 HP
 025 - 25 HP
 030 - 30 HP

11 VOLTAGE
 A = 3/60/208-230/460
 B = 3/60/230-460
 C = 3/60/575
 D = 3/60/200
 E = 3/60/380
 F = 3/60/460
 J = 3/50/190-380
 K = 3/50/208-416
 L = 3/50/220-440
 M = 3/50/200-400

12 RPM
 15 - 1500/60Hz
 18 - 1800/60Hz
 30 - 3000/60Hz
 36 - 3600/60Hz

13 MOTOR TYPE
 T - TEFC
 N TENV
 W - Washdown
 X - Explosion Proof
 C - Chemical Duty
 S - Stainless Steel

15 MANUFACTURER
 W - Weg
 S - Sterling
 R - Reliance
 B - Baldor

15 OPTIONS
 A - No Options
 B - Inverter Duty
 W - White
 P - Premium Efficient

*Refer to pump curves for available impeller sizes by model. Contact Alfa Laval if other options are required.