

Consider the information below when selecting a MR pump.
 Note: The configuration shown below will not reflect the actual model number shown on the Customer Order Acknowledgement.

MR185	M	199	S	0	E	S	21	A	A	N	7P5	A	18	W	S	A
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
MR185	M	199	S	0	E	N	21	A	A	N	-	0	0	0	0	0

- 1 STYLE**
 MR166
MR185
 MR200
 MR300 (NON 3A)
- 2 CONNECTION TYPE**
M - Tri-Clamp®(std)
- 3 IMPELLER SIZE**
 165 = MR166
199 = MR185
 199 = MR200
 240 = MR300
- 4 SEAL TYPE**
S - Single Shaft Seal
- 5 SEAL FACE MATERIAL**
0 = Carbon Vs AISI 329 SS Stationary (MR166, MR185 & MR20)
 0 = AISI 329 SS Vs Carbon Stationary (MR300 only)
 4 = Silicon carbide Vs Silicon carbide (MR185 & MR200 only)
- 6 ELASTOMER MATERIAL**
E - EPDM (std)
 Y - Viton (Fluorinated)
 U - NBR (Nitrite)
- 7 LEG BRACKET**
N - NONE
- 8 MOTOR FRAME**
 18 - 182TC/184TC MR166
21 - 213TC/215TC MR185
 25 - 254TC/256TC MR200
 28 - 286TD MR300
- 9 CASING DRAIN**
A - No Drain
- 10 FINISH OPTIONS**
A = 32 Ra Mech
 B = 20 Ra Mech
 E = Industrial (MR300)
- 11 PASSIVATION**
 Y = Yes
N = No
- 12 HORSE POWER**
 005 - 5 HP (MR-166)
 7P5 - 7.5 HP (MR-185)
 015 - 15 HP (MR-200)
 030 - 30 HP (MR-300)
- 13 VOLTAGE**
 A = 3/60/208-230/460
 B = 3/60/230-460 (15HP or higher)
- 14 RPM**
 18 - 1800/60Hz
- 15 MOTOR TYPE**
 W - Washdown
- 16 MANUFACTURER**
 S - Sterling
 R - Reliance
 B - Boldor
- 17 OPTIONS**
A - No Options

*Refer to pump curves for available impeller sizes by model. Contact Alfa Laval if other options are required.